



A⁺⁺

UPGRADE

+ PRODUCTS

- Application for wine cellar, garbage room, preparation rooms...
- Cooling and heating mode.
- G1 filter.



RCW6

FEATURES

TECHNOLOGY:



DC INVERTER



R410A FILL



ELECTRONIC EXPANSION VALVE

AIR QUALITY / CLEAN:



ANTIBAC TERA FILTER



FRESH AIR

USER FUNCTIONS:



SLEEP MODE



24 H



RESTART



REMOTE CONTROL LOCK

INSTALLER FUNCTIONS:



DIGITAL DISPLAY



SELF DIAGNOSTIC



LEFT/RIGHT DRAIN CONNECTION



ALARM OUTPUT



UNIT ON INPUT



DRY CONTACT ON/OFF



WATER PUMP CONNECTION (OPTIONAL)



BMS COMPATIBLE

- Designed for local low temperature: 12°C minimum.
- Long blowing distance (up to 11 m).
- Guaranteed energy saving through weekly programming.



DEDICATED DESIGN FOR WINE CELLARS OR ANY LOW TEMPERATURE PROCESS ROOMS

OPTIONS

Accessory	Part number	Photo	Function
Central controller RCW16	7ACEL1707		Controls up to 64 indoor units with individual setting failure codes indication, ON-OFF dry contact, last operation memory, Modbus.
BMS gateway	7ACEL1708		Maximum 1024 units could be connected (16 gateways).